

akurit PTB FixUP

Drying accelerator

drying accelerator for paste-like facade plasters

- solvent-free
- has a drying effect at temperatures $\geq +7^{\circ}\text{C}$

Neu!



Applications

- to increase early rain resistance
- for flexible use on the building site, especially in spring and autumn when the day and night temperatures fluctuate wildly
- only to be used in the finish coats AKURIT PSH silicone resin plaster and PDI dispersion plaster
- for external use

Processing

Temperature

- Only use with substrate and air temperatures between $+5^{\circ}\text{C}$ and $+15^{\circ}\text{C}$.
- Only use at a maximum relative humidity of 85 %.

Mixing / Preparing / Processing

- Add AKURIT PTB FixUP drying accelerator and mix directly before processing the finish coat. Process finish coat promptly after adding.
- Dosage: 500 ml per 25 kg of paste-like facade plaster

Drying / Hardening

- The product drying time is highly dependent on temperature, air movement and humidity. As these factors cannot be calculated on the facade, no exact statement can be made about using the accelerator.
- As a matter of principle, in case of unfavourable weather conditions, suitable measures, e.g. rain protection, are to be taken on the facade area to be worked on or freshly created.

Tool cleaning

- Clean all tools and equipment with water immediately after use.

akurit PTB FixUP

Drying accelerator

Notes

- Prevent colour and/or texture differences: Process the material over the whole area with AKURIT FixUP or over the whole area without AKURIT FixUP.
- Adding too much and/or too high a material temperature can lead to the material thickening immediately in the container.
- In case of tinted finish coat versions, the viscosity may already be lowered. In this case add no or less AKURIT PTB FixUP drying accelerator. Make sure that an even quantity is added to all containers.

Packaging

- 500 ml/bottle

Storage

- Store in the original, unopened packaging in dry, frost-free conditions.
- Protect against direct sunlight.
- Can be stored for at least 18 months in sealed original container.

Quantity required / Yield

- dosage: 500 ml per 25 kg of paste-like facade plaster

Safety and disposal instructions

Safety

- In the event of contact with eyes or skin, immediately rinse thoroughly with water.
- Always wear protective gloves and goggles during application.
- Follow further instructions in the safety data sheet.

Disposal

- Completely empty and recycle the packaging.
- Dispose of the material in accordance with the official regulations.

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.