

akurit T-FAL PS

Primer pin

- increases the adhesion rate of the profile
- Easy, quick and even application
- colourless



Applications

- for improving adhesion low-energetic surfaces e.g. paint, wood glazes, epoxy powder coatings and plastic surfaces

Properties

- drip-free
- easy to apply

Processing

Temperature

- Do not use at air, material and substrate temperatures below +5°C and with expected night frost as well as above +40°C, direct sunlight and/or strong winds.

Applying / Processing / Assembling

- Clean the surface being bonded and allow to dry off.
- Apply primer onto the surface being bonded.
- Maintain adequate flash-off time until it has completely dried off.
- Glue profile on from one end of the profile to the other without tension.
- Press on the profile firmly over its entire length to achieve the optimal bond with the substrate.

Storage

- Store in the original, unopened packaging in dry, frost-free conditions.
- If stored in its original packaging, the product will keep for at least 12 months from the date of manufacture.

Packaging

- 1 piece

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.