



PRIME – REPAIR – IMPROVE

G Gypsum

Gypsum for electrical installation and painting work



TECHNICAL INFORMATION

Colour	white
Processing temperature	+5°C up to +35°C
Processing time	approx. 5-10 minutes

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.

PROPERTIES

- rapid hardening

APPLICATIONS

- for sealing dowels and holes
- for compensating unevenness
- for interior use

SUBSTRATE

Cleanse the area to be plastered of dust and loose parts and then moisten the substrate.

PROCESSING

Do not process at air, material and substrate temperatures below +5 °C.

Sprinkle the desired amount of gypsum into clean, cold water (rubber cup or similar) and let it steep for 1 – 2 minutes. Then mix, apply and smooth over immediately with a spatula or a trowel. If necessary, level transitions immediately with a wet brush.

The processing time is about 10 minutes after mixing. Contaminated or warm water and dirty vessels may significantly shorten the processing time.

Clean all tools and equipment with water immediately after use.

CONSUMPTION

consumption: depending on application

STORAGE

Store dry and as per instructions.

PACKAGING

- 1.5 kg/bag
- 3 kg/bag
- 6 kg/bag
- 15 kg/sack

DISPOSAL

Due to the Green Dot, the empty packaging can be disposed of via the Dual System Germany.

NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023



PRIME – REPAIR – IMPROVE

G Gypsum

Gypsum for electrical installation and painting work

EMERGENCY NUMBER: +49 551 19 240

quick-mix is a Sievert brand
Sievert Baustoffe SE & Co. KG
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • info@quick-mix.de • www.quick-mix.de