

akurit VARIO FS

Texturing joint mortar

acrylate sealant with plaster-like texture

- good UV resistance
- colour: white



Applications

- for sealing joints and connections of VARIO reveal elements
- for external and interior use

Properties

- low odour

Substrate

Condition / Testing

- The substrate must be dry, load-bearing, clean, dust-free and free of adhesion-reducing residues, release agents, efflorescence and sintered coatings.

Pretreatment

- Carefully remove adhesion-reducing layers and contamination, e.g. dust, sinter layers, efflorescence or release agent residue, using suitable measures.
- Cleaning non-porous substrates: Cleaning with suitable cleaning agent and clean, lint-free cloth.
- Cleaning porous substrates: Clean loose particles off surfaces mechanically, e.g. with a steel brush or sanding disc.
- Absorbent mineral adhesive surfaces should be dampened with water to improve adhesion.

Processing

Applying / Processing / Assembling

- Apply filling compound evenly using a manual or compressed air gun, press on surface with a dampened tool before a skin starts to form.
- Remove contamination with water whilst fresh.

Processing time

- Skin formation time: approx. 10 minutes
- Timings relate to +23°C and 50% relative humidity.

Subsequent coating / workability

- Can be painted over with AKURIT dispersion paints.

Packaging

- 310 ml/cartridge

Storage

- Store in the original, unopened packaging in dry, frost-free conditions.

akurit VARIO FS

Texturing joint mortar

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.