

BFF Plex

Contraction joint tape

Universal joint tape, easy to cut to length and use on the building site

- heat-resistant for hot-cast joints
- with defined compression hardness and resilience
- frost and de-icing salt-resistant
- roll width: 30 cm



APPLICATIONS

- joint tape made of physically crosslinked polyolefin foam (PE low-expansion foam)
- for producing joint inserts (joint fillers) for contraction joints
- particularly suitable as underfill strip for permanently elastic joint grouting

PROPERTIES

- can be compacted up to at least 60 % of the thickness
- chemical resistant

PACKAGING

- 15 m/roll
- 20 m/roll
- 25 m/roll

GENERAL INFORMATION

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.