



Solvent-free primer for mineral substrates

- red for ease of visual checking
- active period: approx. 30 minutes



APPLICATIONS

- for the improvement of the adhesion of thick bitumen coatings and reactive waterproofing on all mineral substrates
- for consolidating the surface of mineral substrates
- for external and interior use

PROPERTIES

- solvent-free
- ready for use
- rollable and spreadable
- consolidates the subsoil
- dust-binding
- water-repellent
- vapour-permeable
- colored red

SUBSTRATE

Suitable substrates	■ mineral-bound substrates
Properties/tests	■ The substrate must be dry, load-bearing, clean, dust-free and free of adhesion-reducing residues, release agents, efflorescence and sintered coatings. ■ Plasters must be hardened.
Pretreatment	■ Remove loose particles, dust and adhesion-depleting contaminants.

PROCESSING

Temperature	■ Do not use in air or substrate temperatures of less than +5°C and with expected night time frost, or over +30°C, in direct sunlight and/or in strong wind.
Applying	■ quick-mix BGR primer can be painted or rolled ■ The subsequent thick bitumen coating or ADR ALLES DICHT 2K reactive waterproofing can also be applied to the still matt-damp primer (after approx. 30 minutes).
Drying / Hardening	■ Longer drying times do not have a negative effect on the adhesive bond of the subsequent coating, but renewed dust formation must be avoided ■ Protect from adverse weather conditions (frost, rain, etc.).
Notes	■ During the construction phase, no water must get between the substrate and the primer.



PACKAGING

- 5 kg/canister
- 20 kg/canister

STORAGE

- Store in the original, unopened packaging in dry, frost-free conditions.

QUANTITY REQUIRED / YIELD

- consumption: approx. 150 g/m²

SAFETY AND DISPOSAL INSTRUCTIONS

- Completely empty and recycle the packaging.
- Dispose of the material in accordance with the official regulations.

GENERAL INFORMATION

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.